

AISI316 RITEGNO - 655



Valvola di ritegno in acciaio inox AISI 316.
Attacchi filettati F/F.

*Stainless steel AISI 316 check valve.
Threaded ends F/F.*

Clapet de retenue en acier inox AISI 316.
Taraudage pas gaz F/F.


Rückschlagventil aus Edelstahl AISI 316.
Anschlussgewinde I/I.



IMPIEGHI: le 655 sono adatte per impianti industriali, chimici ed alimentari.

APPLICATIONS: The 655 series are suitable for use in industrial, chemical and food plants.

N. N.	DENOMINAZIONE PART NAME	MATERIALE MATERIAL	TRATTAMENTO TREATMENT
1	Corpo - Body	AISI 316	
2	Manicotto - Body end	AISI 316	
3	Molla - Spring	AISI 316	
4	Otturatore - Disc	AISI 316	
5	Guarnizione - Gasket	PTFE	



DN	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
Ø	8	10	15	20	25	30	38	47	61	75	94
A	30.5	30.5	37	42	48	58	70	82	102.5	120	150
S	53	53	56	63	74	81	91	97	118	138	158

Dimensioni in mm - Dimensions in mm

DATI TECNICI - TECHNICAL DATA	
Pressione massima di esercizio Max working pressure	PN64
Temperatura massima di esercizio Max working temperature	-25°C + 180°C
Filettatura estremità Threaded ends	UNI - ISO 228/1

